




## ACCESSORIES & EQUIPMENTS



**GSK Controller**



**Centroid**



**PA 8000**

## CHARACTERISTICS – LK5N

### TABLE

Spindle Taper		ISO 30
Spindle Speed range		20 -4000 rpm
Table Size	mm	1065 x 255
No. of T-Slots	No.	3
Width of T-Slot	mm	14
Center of T-Slot	mm	65
Longitudinal Travel, X	mm	650
Cross Travel, Y	mm	280
Vertical Travel, Z	mm	127
Ram Movement	mm	300
Distance b/w Spindle Nose and table (max)	mm	480
Spindle Motor	HP/KW	3/2.25

### CAPACITY

Drilling dia (Manual)	mm	25
Drilling dia (Power)	mm	10
Boring dia	mm	150
Milling	mm	31
Coolant Pump	HP/KW	0.15/0.11

### WEIGHT & DIMENSIONS

Shipping Volume	Cu-m	5.9
Shipping dimensions	(LXWXH) mm	1512x1572x2485
Net Machine weight	Kg	1400
Gross Weight	Kg	1750

### STANDARD ACCESSORIES

- Inverter Motor Spindle Head
- Coolant System
- Chip Tray
- Halogen Work lamp
- Grease Gun
- Milling Stub Arbor ISO-30
- Servicing Tools
- Instruction Manual
- Electric equipments including motors
- (Main, Feed & Coolant pump)
- 400 V ± 5% 50c/s, 3 phase

### FEATURES

- Combines Efficiency and Economy
- AC Servomotors on X,Y, Z axis
- 3 axis interpolation for Die & Mold applications
- ISO Standard G & M codes
- High precision C3 Ball screws
- Box ways for strength & rigidity
- CNC Control options; PA 8000, Centroid, GSK

### OPTIONAL TOOLS & ACCESSORIES

- Milling Stub Arbors ISO-30
- Transition Sleeve ISO-30
- Collets Holder with Collets set ISO-30
- Rotary Table 250 mm (LAR 025)
- Machine Vice (LAV 018)



**PAKISTAN MACHINE TOOL FACTORY (Pvt.) Ltd.**

PMTF Road, Off National Highway Karachi -75030, Pakistan.

Tel: (92-21) 5082451-54, Fax: (92-21) 5082450

E-mail:md@pmtfl.com, gmbdpmtf@hotmail.com [http:// www.pmtfl.com](http://www.pmtfl.com)

